

EVOLUTION 500 FTX SP 10W-30 is a premium multi-grade motor oil using ELF mineral technology, intended for lubrication of gasoline passenger car engines meeting latest SP/GF-6A standards.

## Technical Data Sheet

International  
Specifications

API SP  
ILSAC GF-6A

\* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

## 1 - Applications

ELF EVOLUTION 500 FTX SP 10W-30 is recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charged technologies.

Suitable for all conditions (in town, on highways or motorways). Meets the needs of motor manufacturers regarding extended oil change intervals.

## 2 - Customer Benefits

Fuel saving

Enhanced start-up performance, prevents sludge build-up and controls oxidation

Fully compatible with all gasoline emission control devices

## 3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	859.9
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	64.8
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.2
Viscosity index	ASTM D2270	-	144
Pour point	ASTM D97	°C	-40
Flash point	ASTM D92	°C	224
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

\* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## 4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## 5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.